Warning

Manufacturer or seller assumes no responsibility for any injuries or damages caused by improper care of the product as decomposition, conversion and transform done by a user voluntarily.

Warning

Do not run wires around or near clutch, brake, or gas pedals. Doing so may cause driving hazards.



1. Red (+)12V Constant
3. Red/White (+)12V Constant
5. Blue (+)Selectable by jumper(Default Ignition)
7. Green (+)12V Ignition(Output/Input)

2. Green/White (+)12V Light
4. White (+)12V Accessory
6. Yellow (+)12V Starter
8. Black GND

Blade Cartridge Connector

1. Green/White (-250mA) LIGHT OUT(POC #1)
2. Blue/Green (-250mA) LOCK OUT(POC #2)
3. Blue (-250mA) UNLOCK OUT(POC #3)
4. Black (-250mA) STATUS OUT(POC #4)
5. Orange (-250mA) REARM OUT(POC #5)
6. Orange/White (-250mA) DISARM OUT(POC #6)
7. White (-250mA) HORN OUT(POC #7)
8. Gray/Black (-) HOOD IN
9. Light Blue/White (+) FOOT BRAKE IN
10. Red/White (-) Trigger Start IN
11. Red (+) Trigger Start IN
12. Yellow/Black (AC) TACH IN


CM-900



S/N: NH00000000001

Made In China

Jumper Setting




4Pin Antenna Port (BLUE 4P)

Thermister Port (BLUE 2P)

UART Port (Black 4P)

DRONE (Gray 4P)



GND	None
(-250mA) LOCK OUT	Blue/Black
(-250mA) UNLOCK OUT	Blue
(-250mA) PRIORITY UL	Orange/Black
(-250mA) TRUNK OUT	Violet/White
(+)12V	None